



## Skjult IP Kamera i Røykvarsler 2p2



[15, 117, 84](#)

**Varenummer:** EX-Hidden-SM 1MP

### Produkt Sammendrag

1MP 720p, Røykvarsler med innebygd IP Kamera

Dual h.264 stream, oppløsning, bildefrekvens, justerbar bithastighet, ONVIF kompatibel, kompatibel med NVR bl.a. Hikvision, Geovision m.fl.

### Produkt Beskrivelse

#### **Technical Specifications:**

Video

## Image Sensor

600TVL CMOS, Color

## Video compression

H.264 high profile, JPEG/BMP snapshot

## Signal system

NTSC/Pal selectable

## Lens

4.3mm pinhole

## Min. Illumination

0.1 Lux (IR OFF), 0 LUX (IR ON)

## Frame rate

30fps NTSC, 25fps Pal

## Resolution

D1 (720x480)

## Video adjustment

Brightness, contrast, & saturation

## Video bit rate

32 Kbps ~ 2.5 Mbps

## Zoom

Digital zoom

## IR cut filter

No

Night vision

No

Recording & Playback

Recording mode

Motion detection, manual, and schedule

Storage

Record to local SD (up to 32GB, not included); record to remote PC; video or snapshot

Backup

Remote back up to PC

Playback

Playback via SD reader; real time remote playback; remotely download and playback

Alarm

Motion detection

VMD (video motion detection)

Alarm reactions

Alarm photo email; record photo to FTP; record video/photo to SD

Network

Network interface

10/100 Base Ethernet (for wired network connection)

## Wireless network

Wi-Fi 802.11 b/g/n

## IP mode

Dynamic IP address; static IP address

## Protocol

TCP/IP, HTTP, TCP, ICMP, UDP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNT, & RTSP.

## Online users

10 users at the same time

## Mobile surveillance

iPhone, Android

## Internet viewing

Supports browsers: IE, Firefox, Chrome and Safari

## Remote access

Yes

## Software

CMS software

Central management software for recording, remote monitoring, remote access and control, search and playback, and up to 64 multiple cameras surveillance

## User levels for CMS

Administrator, Normal, & Guest (viewing only)

## Camera naming

## Supports camera labeling for distinguishing cameras

### Password protection

Yes

### CPU & System

Operating system

Embedded Linux OS

Micro processor

32Bit RISC embedded processor

### System requirement

Microsoft Win98 SE, ME, 2000, XP, Vista, or Windows 7

### Others

Indoor/outdoor usage

Indoor

### Operating temperature

-10 ~ 50 °C (+14 ~ 122 °F)

### Humidity

95% RH

### Power

DC12V 1A

## Produkt Gallery

