



HIKVISION 1.3MP Utendørs Bullet Man Zoom 2.8-12mm AutoIris

[15, 117, 84](#)

Varenummer: 2045451

Produkt Tags: [1.3 Mpix](#), [2.8-12mm](#), [DS-2CD2612F-I \(2.8-12MM\)](#), [Ethernet](#), [Manuell Zoom](#), [Utendørs](#)

Produkt Sammendrag

HIKVISION IR bullet camera 3D DNR DWDR BLC 2.8-12mm auto iris

Produkt Beskrivelse Camera

Image Sensor:

1/3" Progressive Scan CMOS

Minimum Illumination:

0.014 lux@F1.4

0 lux with IR

Shutter Time:

1/30s ~ 1/100,000s

Lens:

2.8 ~ 12 mm @F1.4, angle of view: 80° ~ 28.7°

Lens Mount:

Ø14

Day& Night:

ICR

Digital Noise Reduction:

3D DNR

Wide Dynamic Range:

Digital WDR

Backlight Compensation:

Yes, zone configurable

Compression Standard

Video Compression:

H.264/M-JPEG

H.264 Compression Profile:

Main profile

Bit Rate:

32 Kbps~16Mbps

Image

Max Image Resolution:

1280x960

Frame Rate:

60 Hz: 30 fps (1280 × 960), 30 fps (1280 × 720)

Image Settings:

Saturation, brightness, contrast adjustable through client software or web browser

Network

Network Storage:

NAS

Alarm Trigger:

Motion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage error

Protocols:

TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP, SNMP, FTP, 802.1X, QoS, HTTPS

System Compatibility:

ONVIF, PSIA, CGI

General Functionalities (Security):

User authentication, watermark, dual stream

Interface

Communication Interface:

1 RJ45 10 M/100 M Ethernet port

On-board Storage:

Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB

General

Power Supply:

DC12V \pm 10%, PoE (802.3af)

Power Consumption:

Max. 5.5W (Max. 7.5W with ICR on)

Working Temperature (Operating Conditions):

-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)

IR Range:

Up to 30m

Dimensions:

95 x 105 x 258.6 mm (3.74" x 4.13" x10.18")

Weight:

1200g