



HIKVISION 2MP Utendørs Bullet Motor-Zoom 2.8-12mm



[15,117,84](#)

Varenummer: 2357505

Produkt Tags: [2 Mpix](#), [2.8-12mm](#), [DS-2CD4A20F-IZS\(2.8-12MM\)](#), [Ethernet](#), [Motorized Zoom](#), [Utendørs](#)

Produkt Sammendrag

HIKVISION SMART 2MP Full HD Bullet Camera IR 30meters Motorized VF lens audio/alarm IO built-in Micro SDHC slot IP67 DWDR BNC

Produkt Beskrivelse

Camera

Image Sensor:

|

1/2.8" Progressive Scan CMOS

Min. Illumination:

|

0.01 Lux @ (F1.2, AGC ON), 0 lux with IR

0.014 Lux @ (F1.4, AGC ON), 0 lux with IR

Shutter time:

|

1/3s ~ 1/100,000s

Slow shutter:

|

Support

Lens:

|

2.8-12mm @ F1.4, 113°~33.8°

Day& Night:

|

IR cut filter with auto switch

Wide Dynamic Range:

|

Digital WDR

Compression Standard

Video Compression:

|

H.264/MJPEG

H.264 code profile:

|

Baseline Profile / Main Profile

Video bit rate:

|

32Kbps~8Mbps

Audio Compression:

|

G.711/G.722.1/G.726/MP2L2

Audio bit rate:

|

64Kbps(G.711) / 16Kbps(G.722.1)/ 16Kbps(G.726)/ 32-128Kbps(MP2L2)

Image

Max. Image Resolution:

|

1920 x 1080

Frame Rate:

|

50Hz: 25fps (1920 × 1080) / (1280 × 960) / (1280 × 720)

60Hz: 30fps (1920 × 1080) / (1280 × 960) / (1280 × 720)

Third Stream:

|
Independent with Main Stream and Sub Stream, up to
50Hz: 1fps (1920 × 1080)
60Hz: 1fps (1920 × 1080)

Image Enhancement:

|
BLC/3D DNR/ROI/Defog

Picture Overlay:

|
LOGO picture can be overlaid on video with 128x128 24bit bmp format

Day/Night Switch:

|
Auto/Schedule/Triggered by Alarm In

Network

Network Storage:

|
NAS (Support NFS,SMB/CIFS), ANR

Protocols:

|
TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, U
PnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

System Compatibility:

|
ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI

Interface

Audio:

|
1-ch 3.5 mm audio in (Mic in/Line in)/out interface (-S model)

Communication Interface:

|
1 RJ45 10M / 100M Ethernet interface and 1 RS-485 interface

Alarm:

|
1 input, 1 output (up to DC24V 1A or AC110V 500mA)(-S model)

Video Output:

|
1Vp-p composite output (75 Ω /BNC) (-S model)

On-board storage:

|
Built-in Micro SD/SDHC/SDXC slot, up to 128 GB

Reset Button:

|
Yes

General

Operating Conditions:

|

-30 °C ~ 60 °C (-22 °F ~ 140 °F)

Humidity 95% or less (non-condensing)

Power Supply:

|

12 VDC \pm 10%, PoE (802.3af)

Power Consumption:

|

12W MAX

Weather Proof:

|

IP67

IR Range:

|

Up to 50m

Dimensions:

|

100×103.9×311.8mm (3.94" × 4.09" × 12.28")

Weight:

|

2000 g (4.41 lbs)