



HIKVISION EXIR 4MP Utendørs Bullet I5



Pris: kr 3 790,00

Varenummer: 2449205

Produkt Tags: [4 Mpix](#), [DS-2CD2T42WD-I5\(4MM\)](#), [Ethernet/WLAN](#), [Fast](#), [Utendørs](#)

Produkt Variant

- HIKVISION EXIR 4MP Utendørs Bullet I5 - 6mm ()
- HIKVISION EXIR 4MP Utendørs Bullet I5 - 4mm ()

Produkt Sammendrag

HIKVISION 4MP IR EXIR WDR Bullet 4mm lens 1/3" Prog CMOS EXIR 2688×1520

H.264/MJPEG IP66 3D DNR BLC 120dB WDR IR up to 50m

Produkt Beskrivelse

Camera

Image Sensor:

|

1/3" Progressive Scan CMOS

Min. Illumination:

|

0.01Lux @(F1.2,AGC ON), 0.028Lux @(F2.0,AGC ON), 0 Lux with IR

Shutter time:

|

1/3 s ~ 1/10,000 s

Slow shutter:

|

Support

Lens:

|

(-I3: 4,6mm; -I5: 4,6,12mm; -I8: 6,12,16mm) @F2.0

Lens Mount:

|

M12

Day& Night:

|

IR cut filter with auto switch

Wide Dynamic Range:

|

120 dB

Digital noise reduction:

|

3D DNR

Compression Standard

Video Compression:

|

H.264/MJPEG/H.264+

H.264 code profile:

|

Main Profile

Video bit rate:

|

32Kbps~16Mbps

Image

Max. Image Resolution:

|

2688 × 1520

Frame Rate:

|

50Hz: 20fps (2688×1520), 25fps(1920×1080), 25fps(1280×720)

60Hz: 20fps (2688×1520), 30fps (1920×1080), 30fps(1280×720)

Image Enhancement:

|

BLC/3D DNR/ROI

Image Settings:

|

Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser

Day/Night Switch:

|

Auto/Schedule/Triggered by Alarm In

Network

Network Storage:

|

NAS (Support NFS,SMB/CIFS)

Alarm Trigger:

|

Line Crossing, Intrusion Detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect , IP address conflict, Storage exception

Protocols:

|
TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

Security:

|
Flash-prevention, dual stream, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access

System Compatibility:

|
ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI

Interface

Communication Interface:

|
1 RJ45 10M/100M/1000M Ethernet port

General

Operating Conditions:

|
-30 °C ~ 60 °C (-22 °F ~ 140 °F)
Humidity 95% or less (non-condensing)

Power Supply:

|
12 VDC ± 10%, PoE (802.3af)

Power Consumption:

|
I3: Max. 6W; I5: Max. 7.5W; I8: Max. 10.5W

Weather Proof:

|
IP66

IR Range:

|
-I3: 30 meters
-I5: 50 meters
-I8: 80 meters

Dimensions:

|
299.71 × 86.48 × 85.11(11.8" × 3.4" × 3.35")

Weight:

|
1200g (2.65 lbs)