



HIKVISION 1.3MP Innendørs Dome Motorzoom 2.8-12mm



[15, 117, 84](#)

Varenummer: 2101969

Produkt Tags: [1.3 Mpix](#), [2.8-12mm](#), [DS-2CD4112F-IZ \(2.8-12MM\)](#), [Ethernet](#), [Innendørs](#), [Motorized Zoom](#), [POE](#)

Produkt Sammendrag

HIKVISION SMART 1.3MP Low-light Indoor Dome Camera Motorized VF lens 0 Lux IR B/W IR 30m audio/alarm IO

Produkt Beskrivelse

Camera

Image Sensor:

|

1/3" Progressive Scan CMOS

Signal System:

|

PAL/NTSC

Min. Illumination:

|

0.01 Lux @ (F1.2, AGC ON), 0 lux with IR

0.014 Lux @ (F1.4, AGC ON), 0 lux with IR

Shutter time:

|

1 s to 1/100,000 s

Lens:

|

2.8-12mm @ F1.4, angle of view: 98.4-30.2°

-Z: 2.8-12mm @ F1.4, angle of view: 98.4-30.2°

Lens Mount:

|

φ14

Auto Iris:

|

DC drive

Adjustment Range:

|

Pan:0° - 355°, Tilt: 0° - 75°, Rotation: 0° - 355°

Day& Night:

|

IR cut filter with auto switch

Wide Dynamic Range:

|

Digital WDR

Digital noise reduction:

|

3D DNR

Focus:

|

Motorized VF lens(-Z model)

Compression Standard

Video Compression:

|

H.264+/H.264/MPEG4/MJPEG

Video bit rate:

|

32Kbps~16Mbps

Audio Compression:

|
G.711/G.722.1/G.726/MP2L2

Triple Streams:

|
Yes

Image

Max. Image Resolution:

|
1280 × 1024

Frame Rate:

|
50Hz: 25fps (1280 × 1024), 25fps (1280 × 960), 50fps (1280 × 720)
60Hz: 30fps (1280 × 1024), 30fps (1280 × 960), 60fps (1280 × 720)

Third Stream:

|
Independent with Main Stream and Sub Stream, up to
50Hz: 25fps(1280 × 1024)
60Hz: 30fps (1280 × 1024)

Image Settings:

|
Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser

BLC:

|

Support

HLC:

|

Support

Smart Defog:

|

Support

EIS:

|

Support

ROI:

|

Support

Picture Overlay:

|

128 × 128, BMP 24bit, zone configurable

Network

Network Storage:

|

NAS (Support NFS,SMB/CIFS)

Alarm Trigger:

|

Line crossing detection, Intrusion detection, Defocus detection, Scene change detec

tion, Motion detection, Face detection, Dynamic analysis, Tampering alarm, Network disconnect, IP address conflict, Storage exception

Protocols:

|
TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP,
PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

Security:

|
User Authentication, Watermark, IP address filtering, anonymous access, flickerless,
heartbeat, video mask

System Compatibility:

|
ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI

Interface

Audio Input:

|
1-ch 3.5 mm audio interface, MIC IN/LINE IN

Audio Output:

|
1-ch 3.5mm audio interface

Communication Interface:

|
1 RJ45 10M / 100M Ethernet interface and 1 RS-485 interface

Alarm Input:

|
1

Alarm Output:

|
1

Video Output:

|
1Vp-p Composite Output (75 Ω , BNC)

On-board storage:

|
Built-in Micro SD/SDHC/SDXC slot, up to 128 GB

General

Operating Conditions:

|
-30 °C ~ 60 °C (-22 °F ~ 140 °F)
Humidity 95% or less (non-condensing)

Power Supply:

|
12 VDC \pm 10%, PoE (802.3af)

Power Consumption:

|
Max. 6 W
Max. 9 W(IR: 2W, motorized VF lens: 1W)

Impact Protection:

|

IK10

IR Range:

|

Approx. 10 to 30 meters

Dimensions:

|

Φ 140 × 121.8 mm (Φ 5.51" × 4.80")

Weight:

|

1400 g (3.09 lbs)