



HIKVISION LOW LIGHT 1.3MP Utendørs Dome MotorZoom 2.8-12mm

[15, 117, 84](#)

Varenummer: 2101973

Produkt Tags: [1.3 Mpix](#), [2.8-12mm](#), [DS-2CD4312F-IZS \(2.8-12MM\)](#), [Ethernet](#), [Motorized Zoom](#), [Utendørs](#)

Produkt Sammendrag

HIKVISION SMART 1.3MP Low-light Outdoor Dome Camera 30m IR Motorized VF lens audio/alarm IO built-in Micro SDHC slot

Produkt Beskrivelse

Camera

Image Sensor:

|

1/3" Progressive Scan CMOS

Signal System:

|

PAL/NTSC

Min. Illumination:

|
0.01 Lux @ (F1.2, AGC ON), 0 lux with IR
0.014 Lux @ (F1.4, AGC ON), 0 lux with IR

Shutter time:

|
1 s to 1/100,000 s

Lens:

|
2.8-12mm @ F1.4, angle of view: 98.4-30.2°
-Z: 2.8-12mm @ F1.4, angle of view: 98.4-30.2°
8-32mm @ F1.4, angle of view: 27.8-9.1°

Lens Mount:

|
ø14

Auto Iris:

|
DC drive

Adjustment Range:

|
Pan:0° - 355°, Tilt: 0° - 75°, Rotation: 0° - 355°

Day& Night:

|
IR cut filter with auto switch

Wide Dynamic Range:

|
Digital WDR

Digital noise reduction:

|
3D DNR

Focus:

|
Motorized VF lens(-Z model)

Compression Standard

Video Compression:

|
H.264+/H.264/MPEG4/MJPEG

Video bit rate:

|
32Kbps~16Mbps

Audio Compression:

|
-S: G.711/G.722.1/G.726/MP2L2

Triple Streams:

|
Yes

Image

Max. Image Resolution:

|

1280 × 1024

Frame Rate:

|

50Hz: 25fps (1280 × 1024), 25fps (1280 × 960), 50fps (1280 × 720)

60Hz: 30fps (1280 × 1024), 30fps (1280 × 960), 60fps (1280 × 720)

Third Stream:

|

Independent with Main Stream and Sub Stream, up to

50Hz: 25fps (1280 × 1024)

60Hz: 30fps (1280 × 1024)

Image Settings:

|

Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser

BLC:

|

Support

HLC:

|

Support

Smart Defog:

|

Support

EIS:

|

Support

ROI:

|

Support

Picture Overlay:

|

128 × 128, BMP 24bit, zone configurable

Network

Network Storage:

|

NAS (Support NFS,SMB/CIFS)

Protocols:

|

TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, U
PnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

Security:

|

User authentication, watermark, IP address filtering, anonymous access, reset

System Compatibility:

|

ONVIF, PSIA, CGI, ISAPI

Interface

Communication Interface:

|

1 RJ45 10M / 100M Ethernet interface

On-board storage:

|

Built-in Micro SD/SDHC/SDXC slot, up to 128 GB

General

Operating Conditions:

|

-30 °C – 60 °C (-22 °F – 140 °F)

Humidity 95% or less (non-condensing)

-H: -40 °C – 60 °C (-40 °F – 140 °F) with smart heater on

Power Supply:

|

24 VAC \pm 10% / PoE (802.3af)

Power Consumption:

|

Max. 12.5W

Impact Protection:

|

IEC60068-2-75Eh, 50J; EN50102, IK10

Weather Proof:

|

IP66

IR Range:

|

Approx. 10 to 30 meters

Dimensions:

|

Φ 159.8 × 146 mm (Φ 6.29" × 5.75")

Weight:

|

2100 g (4.62 lbs)

NOTE:

|

* "-S" series support 1-ch audio I/O, 1-ch alarm I/O and 1-ch RS-485 interface