



HIKVISION 1ch Enkoder til Pinhole

[15, 117, 84](#)

Varenummer: 2395139

Produkt Tags: [1ch](#), [DS-2CD6412FWD-C1](#)

Produkt Sammendrag

HIKVISION Encoding box 1 camera connect Base unit only

Produkt Beskrivelse

Camera

Image Sensor:

|

1/3" Progressive Scan CMOS

Min. Illumination:

|

-L10/L20/10/20: Color: 0.037 Lux @(F2.3,AGC ON); B/W: 0.0037Lux @(F2.3,AGC ON)

-L30/30: Color: 0.028 Lux @(F2.0,AGC ON); B/W: 0.0028Lux @(F2.0,AGC ON)

Shutter time:

|

1s ~ 1/100,000s

Lens:

|

-L10/L20/10/20: 2.8/3.7mm@ F2.3, angle of view: 80°/57°

-L30/30: 2.0/2.8/4/6 mm@ F2.0, angle of view: 120°(2.0mm),92°(2.8mm),73° (4mm),46°(6mm)

Lens Mount:

|

M12

Day& Night:

|

Electronic

Wide Dynamic Range:

|

120 dB

Digital noise reduction:

|

3D DNR

Compression Standard

Video Compression:

|

H.264/MPEG4/MJPEG

H.264 code profile:

|

Baseline Profile / Main Profile / High Profile

Video bit rate:

|

32Kbps~16Mbps

Audio Compression:

|

G.711/G.722.1/G.726/MP2L2

Triple Streams:

|

Yes

Image

Max. Image Resolution:

|

1280x960

Frame Rate:

|

50Hz: 25fps (1280 × 960), 25fps (1280 × 720)

60Hz: 30fps (1280 × 960), 30fps (1280 × 720)

Third Stream:

|

only single channel camera supports third stream, which is independent with main stream, up to

50Hz: 25fps (1280 × 960)

60Hz: 30fps (1280 × 960)

Image Settings:

|

Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser

BLC:

|

Yes, zone configurable

Smart Defog:

|

Support

EIS:

|

Support(first channel)

ROI:

|

Up to 4 fixed areas in each stream

Picture Overlay:

|

Support 128 x 128 size BMP with 24-bit depth image overlay, zone configurable

Network

Network Storage:

|

NAS (Support NFS,SMB/CIFS)

Protocols:

|

TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

System Compatibility:

|

ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI

Interface

Audio:

|

1-ch 3.5 mm audio in (Mic in/Line in)/out interface

Communication Interface:

|

1 RJ45 10M/100M Ethernet port, 1 RS-485 interface and 1 RS-232 interface

Alarm Input:

|

1

Alarm Output:

|

1

On-board storage:

|

Built-in Micro SD/SDHC/SDXC slot, up to 128 GB

General

Operating Conditions:

|

-30 °C ~ 60 °C (-22 °F ~ 140 °F)

Humidity 95% or less (non-condensing)

Power Supply:

|

12 VDC \pm 10%, PoE (802.3af)

Power Consumption:

|

Max. 6.5 W

Dimensions:

|

78×105×32mm(3.07"×4.13"×1.26")

Weight:

|

Main body: 210g

Cylindrical lens: 113g(2m), 233g(8m)

L-shaped lens: 99g(2m), 220g(8m)

Tube lens: 129g(2m), 242g(8m)

Package+accessories: 224g