



## HIKVISION 1.3MP Utendørs PTZ 30xZoom



[15, 117, 84](#)

**Varenummer:** 2466131

**Produkt Tags:** [1.3 Mpix](#), [DS-2DF5276-AEL](#), [Ethernet](#), [Utendørs](#)

### Produkt Sammendrag

HIKVISION cam 1,3MP IP 5" PTZ 30x 1/3" progressive Scan CMOS 3D DNR ICR  
1280x960 (EU)

### Produkt Beskrivelse

Camera

### Image Sensor:

|

1/3" Progressive Scan CMOS

### Minimum Illumination:

|

Color : 0.4 lux (F1.6,1/30 sec, 50 IRE, AGC on), B/W : 0.03 lux (F1.6,1/30 sec, 50 IRE, AGC on)

Color : 0.05 lux (F1.6,1/1 sec, 50 IRE, AGC on), B/W : 0.005 lux (F1.6,1/1 sec, 50 IRE, AGC on)

### S/N Ratio:

|

≥ 50dB

### Shutter Time:

|

50Hz: 1-1/30,000s

60Hz: 1-1/30,000s

### Digital Zoom:

|

12X

### Lens

### Focal Length:

|

4.3-129mm, 30x

### Zoom Speed:

|  
Approx.3s(Optical Wide-Tele)

Angle of View:

|  
65.5-2.11 degree (Wide-Tele)

Minimum Working Distance:

|  
10-1500mm(Wide-Tele)

Aperture Range:

|  
F1.6-F5.0

Pan & Tilt

Pan Speed:

|  
Pan Manual Speed: 0.1° -300°/s,  
Pan Preset Speed: 540°/s

Tilt Speed:

|  
Tilt Manual Speed: 0.1°-240°/s,  
Tilt Preset Speed: 400°/s

Patrol:

|  
8 patrols, up to 32 presets per patrol

## Pattern:

|

4 patterns, with the recording time not less than 10 minutes per pattern

## Alarm

### Alarm Input:

|

7 Inputs

### Alarm Output:

|

2 relay outputs, alarm response actions configurable

## Input & Output

### Monitor Output:

|

1.0Vp-p / 75Ω, NTSC (or PAL) composite, BNC

### Audio Input:

|

1 Mic in/Line in interface

Line input: 2-2.4V[p-p]; output impedance: 1KΩ, ±10%

### Audio Output:

|

1 Audio output interface

Line level, impedance: 600Ω

## Network

#### Ethernet:

|

10Base -T, /100Base-TX, RJ45 Connector

#### Max.Image Resolution:

|

1280×960

#### Frame Rate:

|

50Hz:25fps(1280×960), 25fps (1280×720); 60Hz:30fps(1280×960), 30fps (1280×720)

#### Protocols:

|

IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTP, P, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE

#### User/Host Level:

|

Up to 32 users,3 Levels: Administrator, Operator and User

#### General

#### RS-485 Protocols:

|

HIKVISION, Pelco-P, Pelco-D, self-adaptive

#### Power Consumption:

|

-A: 24VAC, max. 40W

-AEL: 24VAC, max. 60W / High-PoE, max. 40W

-A3/AE3: 24VAC / PoE+, max. 25W

#### Working Temperature/Humidity:

|

-A: -30°C ~ 65°C (-22°F ~ 149°F)

-AEL: 24 VAC: -40°C ~ 65°C (-40°F ~ 149°F) / High-PoE: -30°C ~ 65°C (-22°F ~ 149°F)

-A3/AE3: -10°C ~ 50°C (14°F ~ 122°F)

90% or less

#### Dimensions:

|

Φ220×325.5mm (Φ8.66"×12.81")(Outdoor)

Φ183.4×243mm(Φ7.22"×9.57")(Ceiling)

Φ245×236mm(Φ9.65"×9.29")(In-ceiling)

#### Weight (approx.):

|

Approx. 5Kg (11.02lbs)

#### Mount Option:

|

Long-arm wall mount: DS-1601ZJ; Corner mount: DS-1601ZJ-corner;

Pole Mount: DS-1601ZJ-pole; Power box mount:DS-1634ZJ