



HIKVISION 1.3MP Utendørs PTZ D 20xZoom



[15, 117, 84](#)

Varenummer: 2521716

Produkt Tags: [1.3 Mpix](#), [DS-2DE4120I-D](#), [Ethernet](#), [Utendørs](#)

Produkt Sammendrag

HIKVISION 1.3MP PTZ IR 1/3" CMOS

- 1.3MP 20X Network IR PTZ Dome Camera
- 1/3" Progressive Scan CMOS
- 1280 x 960
- 20X Optical Zoom
- DWDR
- 3D intelligent positioning function
- Support EZVIZ cloud P2P

- Up to 100m IR distance
- 12VDC power supply

Produkt Beskrivelse

Camera

Image Sensor:

|

1/3" Progressive Scan CMOS

Effective Pixels:

|

1280(H)x960(V)

Signal System:

|

PAL/NTSC

Minimum Illumination:

|

F1.6, AGC On: Color: 0.05 lux, B/W : 0.01 lux, 0 lux with IR

AGC:

|

Auto/Manual

S/N Ratio:

|

≥ 52dB

BLC:

|

ON/OFF

HLC:

|

Support

WDR:

|

Support

Shutter Time:

|

1-1/10,000s

Day& Night:

|

ICR

Digital Zoom:

|

16X

Privacy Masking:

|

8 privacy masks programmable

Auto Focus:

|

Auto / Semi-automatic / Manual

Lens

Focal Length:

|

4.7-94.0mm, 20x

Zoom Speed:

|

Approx.3s(Optical Wide~Tele)

Angle of View:

|

58.3-3.2 degree (Wide~Tele)

Minimum Working Distance:

|

10~1,000mm(Wide~Tele)

Aperture Range:

|

F1.6~F3.5

Pan & Tilt

Pan Range:

|

360°endless

Pan Speed:

|
Pan Manual Speed: 0.1°~80°/s, Pan Preset Speed: 80°/s

Tilt Range:

|
-15°-90° (Auto Flip)

Tilt Speed:

|
Tilt Manual Speed: 0.1°~80°/s, Tilt Preset Speed: 80°/s

Proportional Zoom:

|
Rotation speed can be adjusted automatically according to zoom multiples

Number of Preset:

|
300

Patrol:

|
8 patrols, up to 32 presets per patrol

Power loss recovery:

|
Support

Park Action:

|
Preset / Patrol / Pattern / Pan scan / Tilt scan / Random scan / Frame scan / Panoram
a scan

PTZ Position Display:

|

ON/OFF

Infrared

IR irradiation distance:

|

100m

IR irradiation angle:

|

Adjustable by zoom

Network

Ethernet:

|

10Base -T, /100Base-TX, RJ45 Connector

Max.Image Resolution:

|

1280×960

Frame Rate:

|

50Hz:25fps(1280×960), 25fps (1280×720),

60Hz:30fps(1280×960), 30fps (1280×720)

Main Stream:

|
50Hz:25fps(1280×960), 25fps (1280×720)
60Hz:30fps(1280×960), 30fps (1280×720)

Sub Stream:

|
50Hz:25fps(704×576), 25fps(352×288), 25fps(320×240);
60Hz:30fps(704×480), 30fps(352×240), 30fps(320×240)

Image Compression:

|
H.264 / MJPEG

ROI encoding:

|
Support 4 areas with adjustable levels

Protocols:

|
IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTS
P, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE

No. of Simultaneous Users:

|
Up to 20 users

Dual Stream:

|
Support

Mini SD Card:

|
Support up to 128GB Micro SD/SDHC/SDXC card. Support Edge recording

User/Host Level:

|
Up to 32 users,3 Levels: Administrator, Operator and User

Security Measures:

|
User authentication (ID and PW),
Host authentication (MAC address)
IP address filtering

EZVIZ:

|
Support

Client GUI

Camera Control:

|
Pan/Tilt, Zoom, Focus, Click centering, Zoom by mouse dragging, Iris, preset calling
and programming, auto mode

Date & Time Display:

|
Time: Week: Date, 6 formats on the Client

Client:

|
Support iVMS-4200

Web Browser:

|

IE 7+, Chrome 18 +, Firefox 5.0 +, Safari 5.02 +

General

Menu Language:

|

English

Power Supply:

|

12V DC

Power Consumption:

|

Max.20W

Working Temperature/Humidity:

|

-30°C ~ 65°C (-22°F ~ 149°F)

Protection Level:

|

IP66 standard (outdoor dome)

TVS 4,000V lightning protection, surge protection and voltage transient protection

Mounting:

|

Various mounting modes optional

Dimensions:

|

Ø164.5(mm)×295(mm)

Weight (approx.):

|

2kg (4.41lbs)

Mount Option:

|

Long-arm wall mount: DS-1602ZJ; Corner mount: DS-1602ZJ-corner; Pole Mount: DS-1602ZJ-pole; Power box mount:DS-1602ZJ-box; Swan-neck mount: DS-1619ZJ