



HIKVISION 2MP Utendørs Mini Pan/Tilt WiFi



DS-2DE3204W-DE

[15, 117, 84](#)

Varenummer: 2521714

Produkt Tags: [2 Mpix](#), [DS-2DE3204W-DE](#), [Ethernet/WLAN](#), [Utendørs](#)

Produkt Sammendrag

HIKVISION 2MP Mini PTZ 2.8mm lens 1/2.8" CMOS 1920x1080 H.264/H.265

Produkt Beskrivelse

Camera

Image Sensor:

|

1/3" Progressive Scan CMOS

Effective Pixels:

|

1920(H)x1080(V)

Minimum Illumination:

|

F1.6, AGC On : Color : 0.05 lux, B/W : 0.01 lux

White Balance:

|

Auto/Manual/ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp

AGC:

|

Auto/Manual

S/N Ratio:

|

≥ 52dB

BLC:

|

ON/OFF

HLC:

|

Support

WDR:

|

Support

Shutter Time:

|

1/1~1/10,000s

Day& Night:

|

ICR

Digital Zoom:

|

16X

Privacy Masking:

|

8 privacy masks programmable

Auto Focus:

|

Auto / Semi-automatic / Manual

Lens

Focal Length:

|

2.8~12mm, 4x

Zoom Speed:

|
Approx.1s(Wide~Tele)

Angle of View:

|
105~33.5 degree (Wide~Tele)

Aperture Range:

|
F1.6 ~F2.7

Pan & Tilt

Pan Range:

|
Pan: 0~350°

Pan Speed:

|
Pan Manual Speed: 0.1°~60°/s, Pan Preset Speed: 60°/s

Tilt Range:

|
Tilt: 0°~90°

Tilt Speed:

|
Tilt Manual Speed: 0.1°~50°/s, Tilt Preset Speed: 50°/s

Proportional Zoom:

|

Rotation speed can be adjusted automatically according to zoom multiples

Number of Preset:

|

300

Alarm

Alarm Input:

|

1channels input

Alarm Output:

|

1 channels output

Alarm Actions:

|

Preset, Recording, Relay output, Upload center, Upload FTP, Email linkage

Input & Output

Audio Input:

|

1 audio input (Mic/Line in), 2~2.4V[p-p]; output impedance: 1K Ω , \pm 10%

Audio Output:

|

1 Audio output interface

Line level, impedance: 600 Ω

Network

Ethernet:

|

10Base -T, /100Base-TX, RJ45 Connector

Max.Image Resolution:

|

1920×1080

Main Stream:

|

50Hz: 25fps(1920×1080), 25fps(1280×960), 25fps (1280×720)

60Hz: 30fps(1920×1080), 30fps(1280×960), 30fps (1280×720)

Image Compression:

|

H.264 / MJPEG

Audio Compression:

|

G.711ulaw/G.711alaw/G.726/MP2L2/G.722

Protocols:

|

IPv4/IPv6, HTTP, HTTPS, 802.1X, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RT
SP, RTP, TCP, UDP,IGMP, ICMP, DHCP, PPPoE

No. of Simultaneous Users:

|

Up to 20 users

Dual Stream:

|

Support

User/Host Level:

|

Up to 32 users,3 Levels: Administrator, Operator and User

Security Measures:

|

User authentication (ID and PW),
Host authentication (MAC address)
IP address filtering

General

Power Supply:

|

12V DC or PoE(Power over Ethernet)

Power Consumption:

|

Max. 8W

Working Temperature/Humidity:

|

-30°C ~ 65°C (-22°F ~ 149°F)

Protection Level:

|

IP66 standard (outdoor dome)

TVS 4,000V lightning protection, surge protection and voltage transient protection

Mounting:

|

Various mounting modes optional

Dimensions:

|

Φ140.7×107.2mm

Weight (approx.):

|

950g

Mount Option:

|

Wall mount: DS-1273ZJ -PT6; In-ceiling Mount: 1227ZJ-PT6; Junction Box: DS-1273ZJ -PT6; Wall Mount: DS-1292ZJ; Wall Mount: DS-1293ZJ