



HIKVISION ULTRA LOW LIGHT 3MP Utendørs PTZ 36xZoom



[15, 117, 84](#)

Varenummer: 2408763

Produkt Tags: [3 Mpix](#), [DS-2DF6236V-AEL](#), [Ethernet](#), [Utendørs](#)

Produkt Sammendrag

HIKVISION IP PTZ Outdoor camera True WDR Smart tracking Smart Detection EIS
24VAC High-PoE Ultra-low temperature

Produkt Beskrivelse

Camera

Image Sensor:

|

1/1.9" HD CMOS sensor

Effective Pixels:

|

1920(H)x1080(V)

Signal System:

|

PAL/NTSC

Minimum Illumination:

|

F1.5, 50IRE, AGC On: Color: 0.002 lux, B/W: 0.0002 lux

White Balance:

|

Auto/Manual/ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp

AGC:

|

Auto/Manual

S/N Ratio:

|

≥ 55dB

BLC:

|

ON/OFF

HLC:

|

Support

Smart defog:

|

Support

WDR:

|

120dB

Shutter Time:

|

50Hz: 1~1/30,000s; 60Hz: 1~1/30,000s

Day& Night:

|

ICR

Digital Zoom:

|

16X

Privacy Masking:

|

24 privacy masks programmable; optional multiple colors and mosaics

Auto Focus:

|

Auto / Semi-automatic / Manual

Lens

Focal Length:

|

5.7-205.2, 36x

Zoom Speed:

|

Approx.3.3s(Optical Wide-Tele)

Angle of View:

|

58.7-2.0 degree (Wide-Tele)

Minimum Working Distance:

|

10-1500mm(Wide-Tele)

Aperture Range:

|

F1.5~F3.4

Pan & Tilt

Pan Range:

|

360°endless

Pan Speed:

|
Pan Manual Speed: 0.1°~300°/s, Pan Preset Speed: 540°/s

Tilt Range:

|
-15°-90° (Auto Flip)

Tilt Speed:

|
Tilt Manual Speed: 0.1°~240°/s, Tilt Preset Speed: 400°/s

Proportional Zoom:

|
Rotation speed can be adjusted automatically according to zoom multiples

Number of Preset:

|
300

Patrol:

|
8 patrols, up to 32 presets per patrol

Pattern:

|
4 patterns, with the recording time not less than 10 minutes per pattern

Power loss recovery:

|
Support

Park Action:

|

Preset / Patrol / Pattern / Pan scan / Tilt scan / Random scan / Frame scan / Panoram
a scan

PTZ Position Display:

|

ON/OFF

Freeze Frame:

|

Support

Smart-tracking:

|

Manual/ Panorama/ Intrusion trigger/ Line crossing trigger/ Region entrance trigger/
Region exiting trigger

Smart tracking when patrol between multiple scenarios

Alarm

Alarm Input:

|

7 Inputs

Alarm Output:

|

2

Alarm Actions:

|

Preset, Patrol, Pattern, Micro SD/SDHC card recording, Relay output, Notification on Client, Send Email, Upload to FTP, Trigger Channel

Input & Output

Monitor Output:

|

1.0Vp-p / 75Ω, NTSC (or PAL) composite, BNC

Audio Input:

|

1 Mic in/Line in interface

Line input: 2-2.4V[p-p]; output impedance: 1KΩ, ±10%

Audio Output:

|

1 Audio output interface

Line level, impedance: 600Ω

Network

Ethernet:

|

10Base -T, /100Base-TX, RJ45 Connector

Max.Image Resolution:

|

1920×1080

Main Stream:

|

50Hz: 25fps(1920×1080), 25fps(1280×960), 25fps (1280×720)

60Hz: 30fps(1920×1080), 30fps(1280×960), 30fps (1280×720)

Sub Stream:

|

50Hz: 25fps(704×576), 25fps (352×288), 25fps (176×144)

60Hz: 30fps(704×480), 30fps (352×240), 30fps (176×120)

Third Stream:

|

50Hz: 25fps(1920×1080, 1280×960, 1280×720, 704×576, 352×288, 176×144)

60Hz: 30fps(1920×1080, 1280×960, 1280×720, 704×480, 352×240, 176×120)

Image Compression:

|

H.264/MJPEG/MPEG4

ROI encoding:

|

Support 24 areas with adjustable levels

Audio Compression:

|

G.711ulaw/G.711alaw/G.726/MP2L2/G.722

Protocols:

|

IPv4/IPv6, HTTP, HTTPS, 802.1X, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE

No. of Simultaneous Users:

|
Up to 20 users

Three-Stream:
|
Support

Mini SD Card:
|
Support up to 128GB Micro SD/SDHC/SDXC card. Support Edge recording

User/Host Level:
|
Up to 32 users,3 Levels: Administrator, Operator and User

Security Measures:
|
User authentication (ID and PW),
Host authentication (MAC address)
IP address filtering

Client GUI

Date & Time Display:
|
Time: Week: Date, 6 formats on the Client

Client:
|
Support iVMS-4200

Web Browser:

|

IE 7+, Chrome 18 +, Firefox 5.0 +, Safari 5.02 +

General

RS-485 Protocols:

|

HIKVISION, Pelco-P, Pelco-D, self-adaptive

Menu Language:

|

English

Power Supply:

|

24 VAC & Hi-PoE

Power Consumption:

|

Max.60W

Working Temperature/Humidity:

|

-40°C ~ 65°C (-40°F ~ 149°F)

Humidity: 90% or less

Protection Level:

|

IP67, IK10, TVS 4,000V lightning protection, surge protection and voltage transient protection

Mounting:

|

Various mounting modes optional

Dimensions:

|

Φ178.3(mm)×331.0(mm) (Φ7.02"×13.03")

Weight (approx.):

|

8kg (approx.)

Mount Option:

|

Long-arm wall mount: DS-1602ZJ; Corner mount: DS-1602ZJ-corner;

Pole Mount: DS-1602ZJ-pole; Power box mount:DS-1602ZJ-box; Swan-neck mount:

DS-1619ZJ