



HIKVISION 4MP Innendørs Pant/Tilt



Pris: kr 4 490,00

Varenummer: 2449201

Produkt Tags: [4 Mpix](#), [DS-2CD2F42FWD-IS\(2.8MM\)](#), [Ethernet/WLAN](#), [Fast](#), [Innendørs](#)

Produkt Variant

- HIKVISION 4MP Innendørs Pant/Tilt - 4mm ()
- HIKVISION 4MP Innendørs Pant/Tilt - 2.8mm ()

Produkt Sammendrag

HIKVISION 4MP IR WDR Mini PT 2.8mm lens 1/3" Prog CMOS 2688x1520
H.264/MJPEG 3D DNR BLC 120dB WDR IR up to 10m audio+alarm I/O

Produkt Beskrivelse

Camera

Image Sensor:

|

1/3" Progressive Scan CMOS

Min. Illumination:

|

0.01Lux @ F1.2, AGC ON , 0.028Lux @ F2.0, AGC ON, 0 Lux with IR

Shutter time:

|

1/3 s to 1/10,000 s

Lens:

|

2.8mm, 4mm, 6mm @ F2.0

Lens Mount:

|

M12

Adjustment Range:

|

Pan: -90° ~ 90°, Tilt: 0° ~ 75°

Day& Night:

|

IR cut filter with auto switch

Wide Dynamic Range:

|

120 dB

Digital noise reduction:

|

3D DNR

Compression Standard

Video Compression:

|

H.264/MJPEG/H.264+

H.264 code profile:

|

Main Profile

Video bit rate:

|

32Kbps~16Mbps

Dual Stream:

|

Yes

Image

Max. Image Resolution:

|

2688 × 1520

Frame Rate:

|

50Hz: 20fps (2688 × 1520), 25fps (1920 × 1080), 25fps (1280 × 960), 25fps (1280 × 720)

60Hz: 20fps (2688 × 1520), 30fps (1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720)

Image Settings:

|

Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser

BLC:

|

Yes, zone configurable

ROI:

|

Support

Network

Network Storage:

|

NAS (Support NFS,SMB/CIFS), ANR

Alarm Trigger:

|

Motion detection, tampering alarm, network disconnect , IP address conflict, storage exception

Protocols:

|

TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

Security:

|

One-key reset, flash-prevention, dual streams, heartbeat, mirror, password protection, privacy mask, Watermark, IP address filtering, Anonymous access

System Compatibility:

|

ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI

Interface

Audio:

|

1-ch 3.5 mm audio in (Mic in/Line in)/out interface (-S model)

Communication Interface:

|

1 RJ45 10M / 100M Ethernet interface

Alarm:

|

1x alarm I/O *only for -S models

On-board storage:

|

Built-in Micro SD/SDHC/SDXC slot, up to 128 GB

Reset Button:

|

Yes

Wi-Fi Specification (-W)

Wireless Standards:

|

IEEE802.11b, 802.11g, 802.11n

Frequency Range:

|

2.4 GHz ~ 2.4835 GHz

Channel Bandwidth:

|

20/40MHz Support

Modulation Mode:

|

802.11b: CCK, QPSK, BPSK

802.11g/n: OFDM

Security:

|
64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS

Transmit Power:

|
11b: 17 ± 1.5 dBm @ 11Mbps
11g: 14 ± 1.5 dBm @ 54Mbps
11n: 12.5 ± 1.5 dBm

Receive Sensitivity:

|
11b: -90dBm @ 11Mbps (Typical)
11g: -75dBm @ 54Mbps (Typical)
11n: -74dBm (Typical)

Transmission Rate:

|
11b: 11Mbps
11g: 54Mbps
11n: up to 150Mbps

Wireless Range:

|
50m(depend on environment)

General

Operating Conditions:

|
-10°C ~ 40°C (14°F ~ 104°F), Humidity 95% or less (non-condensing)

Power Supply:

|

12 VDC \pm 10%, PoE (802.3af)

Power Consumption:

|

Max. 5W (Max. 7 W with IR cut filter on, max. 9W with pan & tilt rotation)

IR Range:

|

10 meters

Dimensions:

|

Φ 119.93 \times 87.08mm

Weight:

|

500g (1.1lbs)

NOTE:

|

"-W" series support Wi-Fi (802.11b/g/n) and the modules with Wi-Fi function don't support the 802.1X protocol.