



HIKVISION 4ch Analog Lagringsenhet

[15, 117, 84](#)

Varenummer: 1868354

Produkt Tags: [4ch](#), [DS-7304HFI-ST](#)

Produkt Sammendrag

HIKVISION DS-7304HFI-ST 4ch DVR video audio input HDMI VGA CVBS spot output
3xUSB 2.0 eSATA RS485 RS232 4SATA Interface

Produkt Beskrivelse

Video/Audio Input

Audio Input:

|

4-ch

Video Compression:

|

H.264

HD-SDI video input:

|

4-ch; HD-SDI interface; (800mVp-p, 75Ω)

Supported HD-SDI Camera Types:

|
1080P /60, 1080P /50, 1080P /30, 1080P /25, 720P /60, 720P /50, 720P /30, 720P /25

Audio Compression:

|
G.711u

Two-way Audio:

|
1-ch RCA(2.0Vp-p, 1kΩ)

Video/Audio Output

CVBS Output:

|
1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480

HDMI/VGA Output:

|
1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz

Recording resolution:

|
Main stream: 1080P / 720P / VGA / 4CIF / CIF; Sub-stream: 4CIF(non-real-time) / CIF / QCIF / QVGA

Frame Rate:

|

Main stream: 1/16 fps ~ Real time frame rate

Sub-stream: 1/16 fps ~ Real time frame rate

Video Bit Rate:

|

32 Kbps-16 Mbps

Stream Type:

|

Video/Video&Audio

Audio Output:

|

2-ch, RCA (Linear, 1KΩ, for VGA output and CVBS output respectively)

Audio Bit Rate:

|

64kbps

Dual Stream:

|

Support

Playback Resolution:

|

1080P / 720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF

Synchronous Playback:

|

4-ch

Network management

Remote connections:

|

128

Network protocols:

|

TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™

Hard Disk Driver

Interface Type:

|

4 SATA interfaces for 4 HDDs; 1 eSATA interface

Capacity:

|

Up to 4TB capacity for each disk

External Interface

Network Interface:

|

1; 10M / 100M / 1000M self-adaptive Ethernet interface

USB Interface:

|

3 USB2.0 interfaces

Serial Interface:

|

1 RJ45 RS-232 interface; 1 RS-485 interface; 1 RS-485 keyboard interface

Alarm Input:

|

16-ch

Alarm Output:

|

4-ch

General

Power Supply:

|

100 ~ 240VAC, 47 ~ 63HZ

Consumption:

|

≤35W (without hard disks)

Working Temperature:

|

-10 °C ~ +55 °C (14 °F ~ 131 °F)

Working Humidity:

|

10% ~ 90%

Chassis:

|

19-inch rack-mounted 2U chassis

Dimensions:

|

440 × 390 × 70 mm

Weight:

|

≤8Kg (without hard disks)