



HIKVISION 8ch Analog Lagringsenhet

[15, 117, 84](#)

Varenummer: 1987777

Produkt Tags: [8ch](#), [DS-7208HWI-SH/A](#)

Produkt Sammendrag

HIKVISION DS-7208HWI-SH/A 8ch DVR 4ch audio input VGA CVBS output 2xUSB 2.0 RS485 1SATA Interface. Alarm input

Produkt Beskrivelse

Video/Audio Input

Audio Input:

|

1-ch

Video Compression:

|

H.264

Analog and HD-TVI video input:

|

8-ch BNC interface (1.0Vp-p, 75 Ω)

Supported camera types:

|

720P/25, 720P/30, CVBS

IP Video Input:

|

2-ch Up to 2MP resolution

Video Input Interface:

|

BNC (1.0 Vp-p, 75Ω)

Audio Compression:

|

G.711u

Audio Input Interface:

|

BNC (2.0 Vp-p, 1 kΩ)

Two-way Audio:

|

1-ch, RCA (2.0 Vp-p, 1 KΩ) (using audio input)

Video/Audio Output

HDMI/VGA Output:

|

1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz

Frame Rate:

|

1/16 fps ~ Real time frame rate

Stream Type:

|

Video/Video&Audio

Two-way Audio:

|

1-ch, RCA (2.0 Vp-p, 1 k Ω) (using the audio input)

Audio Output:

|

1-ch RCA(2.0 Vp-p, 1k Ω)

Audio Bit Rate:

|

64kbps

Dual Stream:

|

Support

Synchronous Playback:

|

8-ch

Network management

Remote connections:

|

128

Network protocols:

|

TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS

Hard Disk Driver

Interface Type:

|

2 SATA Interfaces

External Interface

Network Interface:

|

1; 10M / 100M self-adaptive Ethernet interface

USB Interface:

|

2 USB 2.0 Interfaces

General

Power Supply:

|

12V DC

Consumption:

|
≤ 12W(without hard disks)

Working Temperature:

|
-10 °C ~ +55 °C (14 °F ~ 131 °F)

Working Humidity:

|
10% ~ 90%

Chassis:

|
1U chassis

Dimensions:

|
380 × 290 × 48 mm (14.9 × 11.4 × 1.9 inch)

Weight:

|
≤ 2 kg (4.4 lb) (without hard disks)