



## HIKVISION 4ch Hybrid Lagringsenhet

[15, 117, 84](#)

**Varenummer:** 2320792

**Produkt Tags:** [4ch](#), [DS-7604HI-ST/A](#)

### Produkt Sammendrag

HIK VISION DS-7604HI-ST/A DVR 5MP 4ch +4ch IP video input 1-ch audio input. 1-ch audio output HDMI VGA CVBS output 2xUSB2.0 RS485

### Produkt Beskrivelse

#### Video/Audio Input

#### Video Compression:

|

H.264

#### Analog Video Input:

|

4-ch, BNC(1.0Vp-p, 75Ω), PAL/NTSC adaptive

#### IP Video Input:

|

Up to 8-ch

### Composite Video Input:

|

up to 8-ch (Analog video + IP video)

### Audio Compression:

|

OggVorbis

### Audio Input:

|

1-ch, RCA (2.0Vp-p, 1k $\Omega$ )

### Two-way Audio:

|

1-ch, RCA (2.0 Vp-p, 1 K $\Omega$ ) (Using audio input)

### Video/Audio Output

#### HDMI / VGA output:

|

1920 × 1080 / 60 Hz (1080P), 1600 × 1200 / 60 Hz, 1280 × 1024 / 60 Hz,  
1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz

#### CVBS Output:

|

1-ch, BNC (1.0 Vp-p, 75  $\Omega$ ), resolution: PAL: 704 × 576, NTSC: 704 × 480

#### Recording Resolution:

|

Main stream: WD1 / 4CIF / 2CIF / CIF / QCIF

Sub-stream: CIF / QCIF

Frame Rate:

|

Main stream: 25 fps (P) / 30 fps (N)

Sub-stream: 25 fps (P) / 30 fps (N)

Video Bit Rate:

|

32 Kbps ~ 3 Mbps

Audio Output:

|

1-ch, RCA (Linear, 1 KΩ)

Audio Bit Rate:

|

64 Kbps

Synchronous Playback:

|

8-ch

Dual Stream:

|

Support

Hard Disk Driver

Interface Type:

|

## 1 SATA interface

### Capacity:

|

Up to 4 TB capacity for each disk

### External Interface

#### Network Interface:

|

1, 10M/100M self-adaptive Ethernet interface

#### Serial Interface:

|

1 RS-485 interface, half-duplex

#### USB Interface:

|

2, USB2.0

#### Alarm Input:

|

4-ch

#### Alarm Output:

|

1-ch

### General

#### Power Supply:

|  
12V DC

Consumption:

|  
Max. 10W

Working Temperature:

|  
-10°C~+55°C(14°F~131°F)

Working Humidity:

|  
10%~90%

Chassis:

|  
19-inch rack-mounted 1U chassis

Dimensions:

|  
315 × 242 × 45 mm

Weight(Without HDD):

|  
Approx. 2 kg / 4.4 lb (without hard disk)