



HIKVISION 8ch Hybrid Lagringsenhet

[15, 117, 84](#)

Varenummer: 2320793

Produkt Tags: [8ch](#), [DS-7608HI-ST/A](#)

Produkt Sammendrag

HIK VISION DS-7608HI-ST/A DVR 5MP 8ch +8ch IP video input 4-ch audio input 1-ch audio output HDMI VGA CVBS output 2xUSB2.0.RS485

Produkt Beskrivelse

Video/Audio Input

Video Compression:

|

H.264

Analog Video Input:

|

8-ch, BNC(1.0Vp-p, 75Ω), PAL/NTSC adaptive

IP Video Input:

|

Up to 16-ch

Composite Video Input:

|

up to 16-ch (Analog video + IP video)

Audio Compression:

|

OggVorbis

Audio Input:

|

4-ch, RCA (2.0 Vp-p, 1 K Ω)

Two-way Audio:

|

1-ch, RCA (2.0 Vp-p, 1 K Ω) (Using audio input)

Video/Audio Output

HDMI / VGA output:

|

1920 × 1080 / 60 Hz (1080P), 1600 × 1200 / 60 Hz, 1280 × 1024 / 60 Hz,
1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz

CVBS Output:

|

1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480

Playback Resolution:

|

5MP/3MP/1080p/UXGA/720P/WD1/4CIF/VGA/DCIF/2CIF/CIF/QCIF

Recording Resolution:

|

Main stream: WD1 / 4CIF / 2CIF / CIF / QCIF

Sub-stream: CIF / QCIF

Frame Rate:

|

Main stream: 25 fps (P) / 30 fps (N)

Sub-stream: 25 fps (P) / 30 fps (N)

Video Bit Rate:

|

32 Kbps ~ 3 Mbps

Audio Output:

|

1-ch, RCA (Linear, 1 KΩ)

Audio Bit Rate:

|

64 Kbps

Synchronous Playback:

|

16-ch

Dual Stream:

|

Support

Hard Disk Driver

Interface Type:

|

2 SATA interfaces

Capacity:

|

Up to 4 TB capacity for each disk

External Interface

Network Interface:

|

1, 10M/100/1000M self-adaptive Ethernet interface

Serial Interface:

|

1 RS-485 interface, half-duplex

USB Interface:

|

2, USB2.0

Alarm Input:

|

8-ch

Alarm Output:

|

4-ch

General

Power Supply:

|

12V DC

Consumption:

|

Max. 10W

Working Temperature:

|

-10°C~+55°C(14°F~131°F)

Working Humidity:

|

10%~90%

Chassis:

|

19-inch rack-mounted 1U chassis

Dimensions:

|

315 × 242 × 45 mm

Weight(Without HDD):

|

Approx. 2 kg / 4.4 lb (without hard disk)