



HIKVISION 16ch 160Mbps - 4K IP inkl. 1TB HDD



[15, 117, 84](#)

Varenummer: 2509205

Produkt Tags: [16ch](#), [DS-7616NI-I2](#)

Produkt Sammendrag

HIKVISION NVR med 1TB HDD NVR med 1TB HDD 4K 16ch 2HDD Alarm I/O incl.
160M Incoming Bandwidth

Produkt Beskrivelse

Video/Audio Input

IP video input:

|

16-ch

Two-way audio input:

|

1-ch, RCA (2.0 Vp-p, 1k Ω)

Network

Incoming bandwidth:

|

160Mbps

Outgoing bandwidth:

|

256Mbps

Remote connection:

|

128

Video/Audio Output

HDMI Output:

|

1-ch, resolution: 4K(3840*2160)/60Hz, 4K(3840*2160)/30Hz, 1920*1080P/60Hz, 1600*1200/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60Hz

Recording Resolution:

|

12MP/8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Audio Output:

|

1-ch, RCA (Linear, 1kΩ)

Synchronous Playback:

|

16-ch

VGA Output:

|

1-ch, resolution: 1920*1080P/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60 Hz

Decoding

Live view / Playback:

|

12MP/8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Capability:

|

4-ch@8MP,16-ch@1080P

Hard Disk

SATA:

|

2 SATA interfaces for 2 HDDs

Capacity:

|

Up to 6TB capacity for each HDD

External Interface

Network Interface:

|

1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface

Serial Interface:

|

RS-232

USB Interface:

|

Front panel: 1 × USB 2.0

Rear panel: 1 × USB 3.0

Alarm In:

|

4-ch

Alarm Out:

|

1-ch

General

Power Supply:

|

12 VDC

Consumption(without hard disk and POE):

|

≤15 W

Working Temperature:

|

-10 °C ~ +55 °C (+14 °F ~ + 131 °F)

Working Humidity:

|

10 % ~ 90 %

Chassis:

|

380 chassis

Dimensions:

|

380 × 290 × 45 mm (15.0" × 11.4" × 1.8")

Weight(without HDD):

|

≤ 1 Kg (2.2 lb)