



## HIKVISION 16ch IP (16PoE) 160Mbps inkl. 1TB HDD

[15, 117, 84](#)

**Varenummer:** 2450120

**Produkt Tags:** [16ch](#), [DS-7616NI-E2/16P/A](#)

### Produkt Sammendrag

HIKVISION NVR med 1TB HDD 16ch 2HDD 16poe Alarm I/O Incoming Bandwidth 160Mbps

### Produkt Beskrivelse

#### Video/Audio Input

IP video input:

|

16-ch

Two-way audio input:

|

1-ch, RCA (2.0 Vp-p, 1kΩ)

#### Network

Incoming bandwidth:

|  
160Mbps

Outgoing bandwidth:

|  
80Mbps

Remote connection:

|  
128

Video/Audio Output

HDMI/VGA output:

|  
1-ch, resolution:  
1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz

Recording Resolution:

|  
6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Frame Rate:

|  
Main stream: 50 fps (P) / 60 fps (N)  
Sub-stream: 50 fps (P) / 60 fps (N)

Audio Output:

|  
1-ch, RCA (Linear, 1kΩ)

## Decoding

### Live view / Playback:

|

6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

### Capability:

|

16-ch@4CIF, 12-ch@720P,

6-ch@1080P

## Hard Disk

### SATA:

|

2 SATA interfaces for 2 HDDs

### Capacity:

|

Up to 6TB capacity for each HDD

## External Interface

### Network Interface:

|

1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface

### USB Interface:

|

1 × USB 2.0 and 1 × USB 3.0

## POE

### Interface:

|

8 independent 100 Mbps PoE network interfaces

### Max. Power:

|

120W

### Supported Standard:

|

AF and AT

## General

### Power Supply:

|

100~240V AC

### Consumption(without hard disk and POE):

|

≤ 10W

### Working Temperature:

|

-10 °C ~ +55 °C (+14 °F~ + 131 °F)

### Working Humidity:

|

10 % ~ 90 %

Chassis:

|

380 chassis

Dimensions:

|

380 × 290 × 48mm (15.0 × 11.4 × 1.9 inch)

Weight(without HDD):

|

≤ 1 kg