



## HIKVISION 16ch Smart IP 160Mbps inkl. 1TB HDD

[15, 117, 84](#)

**Varenummer:** 2449220

**Produkt Tags:** [16ch](#), [DS-7716NI-E4](#)

### Produkt Sammendrag

HIKVISION SMART NVR med 1TB HDD 160Mbps Bit Rate Input Max (up to 16-ch IP video) 4 SATA Interfaces alarm I/O 16/4 1.5U case 19"

### Produkt Beskrivelse

#### Video/Audio Input

IP video input:

|

16-ch

Two-way audio input:

|

1-ch, RCA (2.0 Vp-p, 1kΩ)

#### Network

Incoming bandwidth:

|  
160Mbps

Outgoing bandwidth:

|  
80Mbps

Remote connection:

|  
128

Video/Audio Output

HDMI/VGA output:

|  
1-ch, resolution:  
1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz,  
1024 × 768 /60Hz

Recording Resolution:

|  
6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Frame Rate:

|  
Main stream: 50 fps (P) / 60 fps (N)  
Sub-stream: 50 fps (P) / 60 fps (N)

Audio Output:

|  
1-ch, RCA (Linear, 1kΩ)

## Decoding

Live view / Playback:

|

6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Capability:

|

16-ch@4CIF, 12-ch@720P,

6-ch@1080P

Hard Disk

SATA:

|

4 SATA interfaces for 2 HDDs + 1 DVD-R/W (default), or 4HDDs

Capacity:

|

Up to 6TB capacity for each HDD

External Interface

Network Interface:

|

2 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces

Serial Interface:

|

RS-232; RS-485;

### USB Interface:

|

Front panel: 2 × USB 2.0

Rear panel: 1 × USB 3.0

### Alarm In:

|

16-ch

### Alarm Out:

|

4-ch

### General

#### Power Supply:

|

100~240VAC

#### Consumption(without hard disk and POE):

|

≤ 20W

#### Working Temperature:

|

-10 °C ~ +55 °C (+14 °F ~ + 131 °F)

#### Working Humidity:

|

10 % ~ 90 %

Chassis:

|

19-inch rack-mounted 1.5U chassis

Dimensions:

|

445 × 390 × 70mm (17.5 × 15.3 × 2.8 inch)

Weight(without HDD):

|

≤ 4 Kg (8.82 lb)