



## HIKVISION 32ch IP 200Mbps Inkl. 1 TB HDD

[15, 117, 84](#)

**Varenummer:** 2043988

**Produkt Tags:** [32ch](#), [DS-7732NI-ST](#)

### Produkt Sammendrag

HIKVISION SMART NVR med 1TB HDD DS-7732NI-ST 160M inbound bandwidth 5MP resolution rec max 32x IP Cam HDMI/VGA/CVBS output 3 USB 2,0, eSATA

### Produkt Beskrivelse

#### Video/Audio Input

IP video input:

|

32-ch

Two-way audio input:

|

1-ch, BNC(2.0 Vp-p, 1kΩ)

#### Network

Incoming bandwidth:

|  
200Mbps

Outgoing bandwidth:

|  
160Mbps

Remote connection:

|  
128

Video/Audio Output

CVBS Output:

|  
1-ch, BNC(1.0Vp-p, 75Ω)  
Resolution: 704×576(PAL); 704×480(NTSC)

HDMI Output:

|  
1-ch, resolution: 1920\*1080P/60Hz, 1920\*1080P/50Hz, 1600\*1200/60Hz, 1280\*1024/60Hz, 1280\*720/60Hz, 1024\*768/60Hz

Recording Resolution:

|  
6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Audio Output:

|  
2-ch, BNC(Linear Electrical Level, 600Ω)

## Synchronous Playback:

|

16-ch

## VGA Output:

|

1-ch, resolution: 1920\*1080P/60Hz, 1600\*1200/60Hz, 1280\*1024/60Hz, 1280\*720/60Hz, 1024\*768/60Hz

## Decoding

## Live view / Playback:

|

6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

## Capability:

|

16-ch@720P, 8-ch@1080P

## Hard Disk

## SATA:

|

4 SATA interfaces for 2 HDDs + 1 DVD-R/W (default), or 4HDDs

## Interface Type:

|

1 eSATA interface

## Capacity:

|

Up to 6TB capacity for each HDD

## External Interface

### Network Interface:

|

1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface

### Serial Interface:

|

RS-232, RS-485, Keyboard

### USB Interface:

|

3, USB2.0

### Alarm In:

|

16-ch

### Alarm Out:

|

4-ch

## General

### Power Supply:

|

100 ~ 240 VAC, 6.3 A, 50 ~ 60 Hz

### Consumption(without hard disk and POE):

|  
≤ 45 W

Working Temperature:

|  
-10 °C ~ +55 °C (+14 °F ~ + 131 °F)

Working Humidity:

|  
10 % ~ 90 %

Chassis:

|  
19-inch rack-mounted 1.5U chassis

Dimensions:

|  
445 × 390 × 70 mm ( 17.5" × 15.3" × 2.8")

Weight(without HDD):

|  
≤ 4 Kg (8.82 lb)