



## HIKVISION SMART 32ch IP 160Mbps Inkl. 1TB HDD

[15, 117, 84](#)

**Varenummer:** 2449223

**Produkt Tags:** [32ch](#), [DS-7732NI-E4](#)

### Produkt Sammendrag

HIKVISION SMART NVR med 1TB HDD 160Mbps Bit Rate Input Max (up to 32-ch IP video) 4 SATA Interfaces alarm I/O 16/4 1.5U case 19"

Embedded Plug & Play NVR

- Third-party network cameras supported
- Up to 6 Megapixels resolution recording
- HDMI and VGA output at up to 1920×1080P resolution
- 8/16/32-ch network cameras can be connected with 80M/160M/160M incoming bandwidth
- Up to 4 SATA interfaces
- Plug & Play with up to 16 independent PoE network interfaces
- Support network detection, including network delay, packet loss, etc

### Produkt Beskrivelse

#### Video/Audio Input

IP video input:

|

## 32-ch

### Two-way audio input:

|

1-ch, RCA (2.0 Vp-p, 1kΩ)

### Network

#### Incoming bandwidth:

|

160Mbps

#### Outgoing bandwidth:

|

80Mbps

#### Remote connection:

|

128

### Video/Audio Output

#### HDMI/VGA output:

|

1-ch, resolution:

1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz,  
1024 × 768 /60Hz

#### Recording Resolution:

|

6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

## Frame Rate:

|

Main stream: 50 fps (P) / 60 fps (N)

Sub-stream: 50 fps (P) / 60 fps (N)

## Decoding

### Live view / Playback:

|

6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

### Capability:

|

16-ch@4CIF, 12-ch@720P,

6-ch@1080P

## Hard Disk

### SATA:

|

4 SATA interfaces for 2 HDDs + 1 DVD-R/W (default), or 4HDDs

### Capacity:

|

Up to 6TB capacity for each HDD

## External Interface

### Network Interface:

|

## 2 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces

### USB Interface:

|

Front panel: 2 × USB 2.0

Rear panel: 1 × USB 3.0

### Alarm In:

|

16-ch

### Alarm Out:

|

4-ch

### General

### Power Supply:

|

100~240VAC

### Consumption(without hard disk and POE):

|

≤ 20W

### Working Temperature:

|

-10 °C ~ +55 °C (+14 °F ~ + 131 °F)

### Working Humidity:

|

10 % ~ 90 %

Chassis:

|

19-inch rack-mounted 1.5U chassis

Dimensions:

|

445 × 390 × 70mm (17.5 × 15.3 × 2.8 inch)

Weight(without HDD):

|

≤ 4 Kg (8.82 lb)