



HIKVISION 4ch IP (4PoE) 40Mbps inkl. 1TB HDD

[15, 117, 84](#)

Varenummer: 2403337

Produkt Tags: [4ch](#), [DS-7604NI-E1/4P/A](#).

Produkt Sammendrag

HIKVISION NVR med 1TB HDD 4ch 1HDD 4poe Alarm I/O Incoming Bandwidth 25Mbps

Third-party network cameras supported

- Up to 6 Megapixels resolution recording
- HDMI and VGA output at up to 1920×1080P resolution
- 4/8/16-ch network cameras can be connected with 40M/80M/160M incoming bandwidth
- Up to 2 SATA interfaces
- Plug & Play with up to 8/16 independent PoE network interfaces
- Support network detection, including network delay, packet loss, etc.

Produkt Beskrivelse

Video/Audio Input

IP video input:

|

4-ch

Two-way audio input:

|

1-ch, RCA (2.0 Vp-p, 1kΩ)

Network

Incoming bandwidth:

|

40Mbps

Outgoing bandwidth:

|

80Mbps

Remote connection:

|

128

Video/Audio Output

HDMI/VGA output:

|

1-ch, resolution:

1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz

Recording Resolution:

|

6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Frame Rate:

|
Main stream: 50 fps (P) / 60 fps (N)
Sub-stream: 50 fps (P) / 60 fps (N)

Audio Output:

|
1-ch, RCA (Linear, 1kΩ)

Decoding

Live view / Playback:

|
6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Capability:

|
16-ch@4CIF, 12-ch@720P,
6-ch@1080P

Hard Disk

SATA:

|
2 SATA interfaces for 2 HDDs

Capacity:

|
Up to 6TB capacity for each HDD

External Interface

Network Interface:

|
1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface

USB Interface:

|
1 × USB 2.0 and 1 × USB 3.0

POE

Interface:

|
4 independent 100 Mbps PoE network interfaces

Max. Power:

|
120W

Supported Standard:

|
AF and AT

General

Power Supply:

|
100~240V AC

Consumption(without hard disk and POE):

|
≤ 10W

Working Temperature:

|

-10 °C ~ +55 °C (+14 °F ~ + 131 °F)

Working Humidity:

|

10 % ~ 90 %

Chassis:

|

380 chassis

Dimensions:

|

380 × 290 × 48mm (15.0 × 11.4 × 1.9 inch)

Weight(without HDD):

|

≤ 1 kg