



HIKVISION 4ch IP 40Mbps inkl. 1TB HDD

[15, 117, 84](#)

Varenummer: 2393910

Produkt Tags: [4ch](#), [DS-7604NI-E1/A](#)

Produkt Sammendrag

HIKVISION NVR med 1TB HDD 4ch 1HDD Alarm I/O Incoming Bandwidth 25Mbps

Produkt Beskrivelse

Video/Audio Input

IP video input:

|

4-ch

Two-way audio input:

|

1-ch, RCA (2.0 Vp-p, 1kΩ)

Network

Incoming bandwidth:

|

40Mbps

Outgoing bandwidth:

|

80Mbps

Remote connection:

|

32

Video/Audio Output

HDMI/VGA output:

|

1-ch, resolution:

1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz

Recording Resolution:

|

6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Frame Rate:

|

Main stream: 50 fps (P) / 60 fps (N)

Sub-stream: 50 fps (P) / 60 fps (N)

Audio Output:

|

1-ch, RCA (Linear, 1kΩ)

Decoding

Live view / Playback:

|

6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Capability:

|

4-ch@1080P

Hard Disk

SATA:

|

1 SATA interface for 1 HDD

Capacity:

|

Up to 4TB for each disk

External Interface

Network Interface:

|

1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface

USB Interface:

|

1 × USB 2.0 and 1 × USB 3.0

Alarm In:

|

4-ch

Alarm Out:

|

1-ch

General

Power Supply:

|

12V DC

Consumption(without hard disk and POE):

|

≤ 10W

Working Temperature:

|

-10 °C ~ +55 °C (+14 °F ~ + 131 °F)

Working Humidity:

|

10 % ~ 90 %

Chassis:

|

2U chassis

Dimensions:

|

315 × 230 × 45 mm (12.4 × 9.0 × 1.8 inch)

Weight(without HDD):

|

≤ 1 kg