



## HIKVISION 64ch 4K IP 320Mbps Inkl. 1 TB HDD

[15, 117, 84](#)

**Varenummer:** 2501016

**Produkt Tags:** [64ch](#), [DS-9664NI-I8](#)

### Produkt Sammendrag

HIKVISION NVR med 1TB HDD 64ch 5MP CD-RW/DVD-RW+4HDD 160M inbound bandwidth 160M outbound bandwidth HDMI VGA CVBS video out 3 USB 2.0

### Produkt Beskrivelse

#### Video/Audio Input

IP video input:

|

64-ch

Two-way audio input:

|

1-ch, RCA (2.0 Vp-p, 1kΩ)

#### Network

Incoming bandwidth:

|  
320Mbps or 200Mbps(when RAID is enabled)

Outgoing bandwidth:

|  
256Mbps or 200Mbps(when RAID is enabled)

Remote connection:

|  
128

Video/Audio Output

HDMI/VGA output:

|  
2-ch, resolution:  
HDMI1/VGA1:HDMI1: 4K (3840 × 2160)/60Hz,  
4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080p/60Hz, 1600 × 1200  
/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz  
VGA1: 2K (2560 × 1440)/60Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 10  
24/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz  
HDMI2/VGA2:1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 76  
8/60Hz

Recording Resolution:

|  
12MP/8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Audio Output:

|  
2-ch, RCA (2.0Vp-p, 1KΩ)

### Synchronous Playback:

|

16-ch

### Decoding

### Live view / Playback:

|

12MP/8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF

### Capability:

|

4-ch@8MP,16-ch@1080P

### Hard Disk

### SATA:

|

8 SATA interfaces for 8 HDDs

### Interface Type:

|

1 eSATA interface

### Capacity:

|

Up to 6TB capacity for each HDD

### Disk array

### Array type:

|

RAID0, RAID1, RAID5, RAID10

### Number of array:

|

4

### External Interface

#### Network Interface:

|

2 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces

#### Serial Interface:

|

RS-232, RS-485, Keyboard

#### USB Interface:

|

Front panel: 2 × USB 2.0

Rear panel: 1 × USB 3.0

#### Alarm In:

|

16-ch

#### Alarm Out:

|

4-ch

## General

### Power Supply:

|

100 to 240 VAC, 50 to 60 Hz

### Consumption(without hard disk and POE):

|

≤30 W

### Working Temperature:

|

-10 °C ~ +55 °C (+14 °F~ + 131 °F)

### Working Humidity:

|

10 % ~ 90 %

### Chassis:

|

19-inch rack-mounted 2U chassis

### Dimensions:

|

445 × 470 ×90 mm (17.5"× 18.5" × 3.5")