



HIKVISION 64ch IP 200Mbps Inkl. 1TB HDD

[15, 117, 84](#)

Varenummer: 2383096

Produkt Tags: [64ch](#), [DS-9664NI-ST](#)

Produkt Sammendrag

HIKVISION NVR med 1TB HDD 64ch 5MP CD-RW/DVD-RW+4HDD 160M inbound bandwidth 160M outbound bandwidth HDMI VGA CVBS video out 3 USB 2.0

Produkt Beskrivelse

Video/Audio Input

IP video input:

|

64-ch

Two-way audio input:

|

1-ch, BNC(2.0 Vp-p, 1kΩ)

Network

Incoming bandwidth:

|
200Mbps

Outgoing bandwidth:

|
160Mbps

Remote connection:

|
128

Video/Audio Output

CVBS Output:

|
1-ch, BNC(1.0Vp-p, 75Ω)
Resolution: 704×576(PAL); 704×480(NTSC)

HDMI Output:

|
1-ch, resolution: 1920*1080P/60Hz, 1920*1080P/50Hz, 1600*1200/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60Hz

Recording Resolution:

|
6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Audio Output:

|
2-ch, BNC(Linear Electrical Level, 600Ω)

Synchronous Playback:

|

16-ch

VGA Output:

|

1-ch, resolution: 1920*1080P/60Hz, 1600*1200/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60Hz

Decoding

Live view / Playback:

|

6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Capability:

|

16-ch@720P, 8-ch@1080P

Hard Disk

SATA:

|

8 SATA interfaces for 4 HDDs + 1 DVD-R/W (default), or 8HDDs

Interface Type:

|

1 eSATA interface

Capacity:

|

Up to 6TB capacity for each HDD

External Interface

Network Interface:

|

2 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces

Serial Interface:

|

RS-232, RS-485, Keyboard

USB Interface:

|

3, USB2.0

Alarm In:

|

16-ch

Alarm Out:

|

4-ch

General

Power Supply:

|

100 ~ 240 VAC, 6.3A, 50 ~ 60Hz

Consumption(without hard disk and POE):

|
≤45W

Working Temperature:

|
-10 °C ~ +55 °C (+14 °F ~ + 131 °F)

Working Humidity:

|
10 % ~ 90 %

Chassis:

|
19-inch rack-mounted 2U chassis

Dimensions:

|
445 × 470 × 90 mm

Weight(without HDD):

|
≤ 8 kg /17.64 lb (without hard disk or DVD-R/W)