



## HIKVISION 4K 8ch IP (8Poe) 80Mbps Inkl. 1TB HDD

[15, 117, 84](#)

**Varenummer:** 2509204

**Produkt Tags:** [8ch](#), [DS-7608NI-I2/8P](#)

### Produkt Sammendrag

HIKVISION NVR med 1TB HDD 4K 8ch 2HDD 8poe Alarm I/O incl. 80M Incoming Bandwidth

### Produkt Beskrivelse

#### Video/Audio Input

IP video input:

|

8-ch

Two-way audio input:

|

1-ch, RCA (2.0 Vp-p, 1kΩ)

#### Network

Incoming bandwidth:

|  
80Mbps

Outgoing bandwidth:

|  
256Mbps

Remote connection:

|  
128

Video/Audio Output

HDMI Output:

|  
1-ch, resolution: 4K(3840\*2160)/60Hz, 4K(3840\*2160)/30Hz, 1920\*1080P/60Hz, 1600\*1200/60Hz, 1280\*1024/60Hz, 1280\*720/60Hz, 1024\*768/60Hz

Recording Resolution:

|  
12MP/8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Audio Output:

|  
1-ch, RCA (Linear, 1kΩ)

Synchronous Playback:

|  
8-ch

VGA Output:

|  
1-ch, resolution: 1920\*1080P/60Hz, 1280\*1024/60Hz, 1280\*720/60Hz, 1024\*768/60 Hz

## Decoding

Live view / Playback:

|  
12MP/8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Capability:

|  
4-ch@8MP,16-ch@1080P

## Hard Disk

SATA:

|  
2 SATA interfaces for 2 HDDs

Capacity:

|  
Up to 6TB capacity for each HDD

## External Interface

Network Interface:

|  
1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface

Serial Interface:

|  
RS-232

#### USB Interface:

|  
Front panel: 1 × USB 2.0  
Rear panel: 1 × USB 3.0

#### Alarm In:

|  
4-ch

#### Alarm Out:

|  
1-ch

#### POE

#### Interface:

|  
8 independent 10 /100 Mbps PoE Ethernet interfaces

#### Max. Power:

|  
120W

#### Supported Standard:

|  
AF and AT

#### General

Power Supply:

|

100 to 240 VAC, 50 to 60 Hz

Consumption(without hard disk and POE):

|

≤15 W

Working Temperature:

|

-10 °C ~ +55 °C (+14 °F~ + 131 °F)

Working Humidity:

|

10 % ~ 90 %

Chassis:

|

380 chassis

Dimensions:

|

380 × 290 × 45 mm (15.0" × 11.4" × 1.8")

Weight(without HDD):

|

≤ 3 Kg (6.6 lb)