



HIKVISION 8ch IP (8PoE) 80Mbps Inkl. 1TB HDD

[15](#), [117](#), [84](#)

Varenummer: 2403340

Produkt Tags: [8ch](#), [DS-7608NI-E2/8P/A](#)

Produkt Sammendrag

HIKVISION NVR med 1TB HDD 8ch 2HDD 8poe Alarm I/O Incoming Bandwidth 50Mbps

Produkt Beskrivelse

Video/Audio Input

IP video input:

|

8-ch

Two-way audio input:

|

1-ch, RCA (2.0 Vp-p, 1kΩ)

Network

Incoming bandwidth:

|
80Mbps

Outgoing bandwidth:

|
256Mbps

Remote connection:

|
128

Video/Audio Output

HDMI Output:

|
1-ch, resolution: 4K(3840*2160)/60Hz, 4K(3840*2160)/30Hz, 1920*1080P/60Hz, 1600*1200/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60Hz

Recording Resolution:

|
12MP/8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Audio Output:

|
1-ch, RCA (Linear, 1kΩ)

Synchronous Playback:

|
8-ch

VGA Output:

|
1-ch, resolution: 1920*1080P/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60 Hz

Decoding

Live view / Playback:

|
12MP/8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Capability:

|
4-ch@8MP,16-ch@1080P

Hard Disk

SATA:

|
2 SATA interfaces for 2 HDDs

Capacity:

|
Up to 6TB capacity for each HDD

External Interface

Network Interface:

|
1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface

Serial Interface:

|
RS-232

USB Interface:

|
Front panel: 1 × USB 2.0
Rear panel: 1 × USB 3.0

Alarm In:

|
4-ch

Alarm Out:

|
1-ch

POE

Interface:

|
8 independent 10 /100 Mbps PoE Ethernet interfaces

Max. Power:

|
120W

Supported Standard:

|
AF and AT

General

Power Supply:

|

100 to 240 VAC, 50 to 60 Hz

Consumption(without hard disk and POE):

|

≤15 W

Working Temperature:

|

-10 °C ~ +55 °C (+14 °F~ + 131 °F)

Working Humidity:

|

10 % ~ 90 %

Chassis:

|

380 chassis

Dimensions:

|

380 × 290 ×45 mm (15.0"× 11.4" × 1.8")

Weight(without HDD):

|

≤ 3 Kg (6.6 lb)